

Performance Enhancements for Mass Flow Controllers

April 25, 2013



DICHTOMATIK

Derby, UK ([RPRN](#)) 04/25/13 — Digital Mass Flow Controllers (MFC's), as typically used in the semiconductor, chemical processing, food and pharmaceutical industries, are designed to both measure and control the flow of various gases and liquids. Applications also

occur where MFC's are used in analytical laboratories for High Pressure Liquid Chromatography. In many applications the gases and fluids are operating at modest temperatures up to 80° C, but can include aggressive media flows which necessitate the use of specialised chemical-resistant elastomer seals.

Most gas flow meters are equipped with seals made of [DuPont™ Viton® fluoroelastomer](#). However MFC's need O-ring seals and other custom parts that do not swell in the presence of more aggressive chemicals utilised within their wide range of industrial applications. The sealing specialist [Dichtomatik Ltd, is an authorised distributor for the DuPont™ Kalrez® range](#) of sealing products, designed to give extended performance when operating with the widest range of chemicals, even incorporating elevated temperature conditions. Tests undertaken with an MFC, fitted with DuPont™ Kalrez® Spectrum™ 6375 O-rings and custom parts, increased reliability of operation and the overall Meantime Between Failures (MTBF) of the equipment.

This increased reliability ensured a competitive advantage for the MFC manufacturer and a commercial advantage for the equipment user, as it reduced production down-times. A logistics saving was also achieved as the standardisation on [Kalrez® parts](#) for all the site modules led to a reduction in the worldwide inventory of different elastomer seals types for the company. A typical selection of [specialised Kalrez® Spectrum™ seals](#) and their particular qualities are detailed, offering minimal swell in various liquids, together with extended lifetime and performance characteristics:



Ref 6375 - for broadest chemical resistance

Ref 7075 - for highest service temperature (up to 327°C) and lowest compression set

Ref 7090 - for high hardness/higher module properties

Ref 3018 - general use in the chemical process and oil exploration industries

Ref 8085 - excellent mechanical strength, very low particle generation and longer seal life

Ref 9100 - for PECVD and HDPCVD processes, offering thermal stability, low erosion, good mechanical strength and excellent elastic recovery

Ref 6230 - superior chemical resistance and low contamination from extractables where FDA compliance is required

Further information is available from:

Dichtomatik Ltd, Donington House, Riverside Road, Pride Park, Derby DE24

8HX

Media Contact Name: Dean Spencer

Media E-mail: dean@grapevine-marketing.co.uk

Media Phone: 01332 253840

Media Web Address: <http://www.grapevine-group.co.uk>

Company Contact Name: Nick Taylor

Company E-mail: nick@dichtomatik.co.uk

Company Phone: 01332 524401

Company Web Address: <http://www.dichtomatik-kalrez.co.uk>

Filed Under: [BREAKING NEWS](#), [BUSINESS NEWS](#), [PRESS RELEASE](#)

RUSH PR NEWS newswire and press release services at rushprnews.com /
Anne Howard annehowardpublicist.com

Content- Legal Responsibility - All material is copyrighted - You may repost but you MUST link back to the original post on your page and acknowledge Rush PR News as the news source. Rush PR News is not legally and/or morally responsible for content of press releases, opinions expressed or fact-checking.

Rush PR News cannot be held legally responsible for material published and distributed through its newswire service or published in its press-room and therefore cannot be sued for published material. Third-party must be contacted directly to dispute content.

Rush PR News is not the contact for material published.